Waste-exit

DD VAC Vacuum units



Direct drive vacuum units:

The DDVAC series is the most popular vacuum unit in our programme. The unit don't need any maintenance, because it's a direct drive. The vacuum unit is available in models from 1.000m³ up to 15.000 m³.

Perfect for Frequency converter control:

The frequency converter ensures that the vacuum unit is working at the same pressure level all the time and in the most economical way. The power saving can be up to 20-40%.

Standard silencing configuration:

All DDVAC vacuum units are fitted with an inlet and exhaust silencer, to minimize the noise level of the unit.

Optional acoustic/outdoor housing:

With the noise reducing cabinet, it's possible to install the unit inside the factory. The cabinet is made of galvanized steel and aluminium so it can be used outside as well as weather protection housing.

Standard type	es: Kwh	m3	Ps/pa.
50 Hz. units			
DDVAC 200.504	4,0	1-3.000	4.000-3.500
DDVAC 250.511	15,0	2-6.500	6.000-5.500
DDVAC 280.518	18,5	4-7.000	7.450-6.800
DDVAC 280.537	37,0	4-13.500	6.500-4.500
DDVAC 315.522	22,0	3-6.000	8.800-10.000
DDVAC 315.530	30,0	6-9.000	8.800-10.000
DDVAC 315.545	45,0	9-14.000	8.800-10.000
60 Hz. units			
DDVAC 200.507	7,0	1-3.000	4.500-4.000
DDVAC 220.611	11,0	2-4.500	5.800-5.200
DDVAC 250.618	18,5	3-6.000	8.700-7.700
DDVAC 280.630	30,0	4-9.000	10.500-8.900
DDVAC 280.645	45,0	9-13.500	9.900-8.700



www.waste-exit.dk Phone: +45 9713 1899 e-mail: sales@ibjuncker.dk Finlandsvej 4, DK 7480 Vildbjerg

Ib Juncker engineering Aps.