

## Separation unit SP 005 716 series.



### Technical data:

#### Models:

- C type (continuous vacuum)
- A type (automatic emptying)
- SA type (semiautomatic emptying)

Filter types:	Flat	or	Panel 50(H)
Filter area:	1,7 m <sup>2</sup>	or	5,5 m <sup>2</sup>
Air capacity:	6.500 m <sup>3</sup> /h	or	8.500 m <sup>3</sup> /h

Dimensions:	2460(L)*1300(W)*2770(H)		
Weight:	825 kg		

#### Integrated vacuum unit sizes:

DDVAC200	2*7,5Kw	6.500m <sup>3</sup> /h	6.500pa
DDVAC200	2*4,0Kw	4.500m <sup>3</sup> /h	4.500pa

#### System control:

A-30 controller  
7" touch screen



### Function of the separation unit:

The separators are designed for fully automatic waste processing and dump it into a container or a compactor, without any manual handling. The operation is fully automatic and there is no daily maintenance on the system.

C- type separator has continuous vacuum, also during the emptying process. This is used for installations where continuous vacuum is needed like in sewing rooms, hosiery knitting and quilting machines.

A- type separator stops the suction under the emptying process. This is mainly used for cutting room installations and sewing rooms with low waste volume.

SA- type works as A-type with timer controlled emptying and smaller controller type A40 or A50